

June, 2016

Product Quick Guide 2016 Spring/Summer –Errata Sheet

The following are specification updates to the PQG2016_Spring_FINAL.pdf

Professional Solutions

Page 7

DS-2CD4125-FWD-IZ change model to DS-2CD4125FWD-IZ

Page 10

DS-2CD4535FWD-IZH/8 change compression, remove MPEG4

Page 11

All Fisheye DS-2CD63xx change IR Range max: to 15 meters

Value Solutions

Page 18

DS-2CD2E10F, DS-2CD2E20F, change Day/Night to Electronic

DS-2CD2512/32F-I, Remove Alarm I/O

Page 21

DS-2DE3304W-DE, change Preset Pan: 30°/sec, Tilt 25°/sec

Page 22

DS-7616NI-I2/8P, change model to DS-7616NI-I2/16P

DS-7716NI-SP/16 and DS-7716NI-I4/16 change image

TurboHD

Page 25

DS-2CE56D1T-AVFIR, change Video out to HD-TVI, change lens to manual not motorized, change Ratings to UL/cUL Listed, change Operating Temperature Range to -20° C to 45° C (-4° F to 113° F), change Power requirements to; 12 VDC, 24 VAC, 4 W

Page 26

DS-2CE56D5T-AVPIR3ZH, change Ratings to IP66/IK10, UL/cUL Listed

DS-2CE56C5T-IT1, change Lens to Fixed, 3.6 mm @ f/2.5 (2.8 mm, 6 mm, 8mm option)

Page 27

DS-2CE16C5T-IT1, change Lens to Fixed, 3.6 mm @ f/2.5 (2.8 mm, 6 mm, 8mm option)

Page 28

DS-2AE4223T-A, change image

Page 29

DS-7204HGHI-SH, DS-7208HGHI-SH, Remove RAID 0, RAID 1, RAID 5, RAID 10

DS-9008HQHI-SH, change Max Incoming/Outgoing Bandwidth to 160 (160 with RAID)

DS-9016HQHI-SH, change Max Incoming/Outgoing Bandwidth to 260 (260 with RAID)

Accessories

Page 31

Monitors – Remove row marked “Criteria”

Page 33

PMPL, change description to Pole Mount Large (requires JBP-W)

CMPL, change description to Corner Mount Large (requires JBP-W)

PMP, change description to Pole Mount Adapter PTZ

Page 34-35, Bracket Chart – See attached changes